

Custom Wastewater Control Panels

<input type="checkbox"/>	SYSTEM TYPE							
	WS = Wastewater Simplex WD = Wastewater Duplex (pump alternation and two pump operation)							
<input type="checkbox"/>	PHASE							
	1P = Single Phase 3P = Three Phase							
<input type="checkbox"/>	ENCLOSURE TYPE							
	P = Polycarbonate NEMA 4X (Weatherproof) Visible Features S = Stainless Steel Type 304 M = Metal, NEMA 1 (Indoor)							
<input type="checkbox"/>	VOLTAGE							
	0 = 120/208/240V 1 = 120V only 2 = 240V only 3 = 480V (includes main disconnect, must select three phase)							
<input type="checkbox"/>	ALARM							
	0 = No Alarm 1 = Alarm (Includes test, silence, alarm dry contacts, red beacon and horn)							
<input type="checkbox"/>	PUMP PROTECTION							
	0 = No Pump Protection (Not an option for duplex panels) 1 = circuit breaker (circuit breakers are included for any duplex unit) 2 = red pump fault light(s) (red pump fault lights are included for any duplex unit), includes pump fault dry contact with pump signal dry contact (seal failure, motor fault, etc.)							
<input type="checkbox"/>	FLOATS							
	X = 0 Floats S = Standard (3 floats for simplex, 4 floats for duplex if alarm selected) O = Other: specify, call factory for details							
<input type="checkbox"/>	PUMP FULL LOAD AMPS							
	0 = 0-8FLA 1 = 8-16FLA 2 = 16-20 FLA 3 = 20-30 FLA							
OPTIONS: _____								

- 1A_ Dial-An-Amp for pump overload specify lockout amperage after letter A example: 1A15
- 2A_ Longer cord length on floats (standard: 20') Specify each float length after letter A example: 2A30
- 3A Pump run dry contact
- 4A Cycle Counter with Reset
- 5A Elapsed Time Meter
- 6A Red Beacon only/no horn (must select no alarm)
- 6B Horn Only/no Red beacon (must select no alarm)

- 5C Alarm Flasher
- 6A Power On LCD Light (Included)
- 6B Green Pump Run LCD Light(s) (Included)
- 6C HOA Switch(es) (included)
- 7A Lockable Latches (included)
- 8A Two pump and high liquid alarm as third float (duplex models only)
- 9A Anti Condensation Heater
- 10A Alarm to be an Oil Smart Alarm

Ordering Example: WD 3P P 3 1 ---- S 2 3A4A

Wastewater Duplex, Three Phase, Polycarbonate Enclosure, 480, Alarm,
---(Pump Protection Included for all Duplex Systems), Standard (4) Float Setup,
Pump Full Load Amps: 16-20 FLA, Pump Run Dry Contact, Cycle Counter with Reset

Simplex Standard Enclosure: 8"x4"x4", 10"x8"x6" Duplex Standard Enclosure: 10"x8"x6" or 12"x10"x6"
May be fee for panel upsize depending on the selected options.

At SEewater, Custom Controls are Standard. We will work with you to meet or exceed any specifications.