

2007-2008 Price Sheet Detailed

Suggested List Price

2007-2008

Pump Controllers

Oil Smart® “Controller Switch” models: 120VAC and 230VAC European for loads up to 1HP
Maximum load hard wires 3/4HP with Piggyback plug. Mounting brackets included with all products.

Standard 2.5” or optional 6” ON & OFF – differential, **Add a 6** to model # when ordering 6” differential no additional cost.

<u>Model#</u>	<u>Description</u>	<u>Suggested Retail</u>
#OSS20R	Motor controller 20’ cord 1 HP Maximum load Hard Wire	\$510.00
#OSS20PBPR	Controller 20’ cord 3/4 HP Maximum load & piggyback plug	\$538.00

Alarms

OSA-05: Oil Smart® Alarm: complete with all mounting hardware 120 volt 15 AMPS maximum GFC1 circuit. Indoor or outdoor NEMA 4X enclosure dimensions 6x5x2.5 exterior alarm test and silence switch. Automatic reset, red beacon alarm light and audible alarm test. 71 decibels buzzer and dry contacts, yellow light to indicate the presence of oil with dry contact. White light to indicate the presence of water with dry contact. Accessible terminal block for dry contacts, Liquid Smart® sensor with 20’ cord and 15’ power cord with plug.

<u>Model#</u>	<u>Suggested Retail</u>
# OSA-05	\$534.50

OSA-06: Oil Smart® Alarm and junction box, Lights and dry contacts with terminal block and grounding lug. Recommended use: With stand-alone Oil Smart® pump controller up to 1 HP or less loads, (Simplex panel is not needed).

Indoor or outdoor NEMA 4X enclosure dimensions 6” x 6” x 4”. Alarm test and silence switch, automatic reset, red beacon alarm light and audible alarm 83 decibels buzzer, and dry contacts, yellow light to indicate the presence of oil with dry contact, white light to indicate the presence of water with dry contact. Includes Liquid Smart® sensor with 20’ cord.

<u>Model#</u>	<u>Suggested Retail</u>
# OSA-06	\$610.50

2007-2008 Price Sheet Detailed

OSA-W: Remote Oil Smart® Solar Alarm. Lights and dry contacts with terminal block and grounding lug. Power provided by Solar Panel and Battery Provided. NEMA 4X enclosure dimensions 6" x 6" x 4". Alarm test and silence switch, automatic reset, red beacon alarm light and audible alarm 83 decibels buzzer, and dry contacts, yellow light to indicate the presence of oil with dry contact, white light to indicate the presence of water with dry contact.

Includes Remote Liquid Smart® sensor with 20' cord.

Model#	Suggested Retail
# OSA-W	\$779.00

Oil Smart® Control Panels (Include Pump Controller and Alarm)

OIL SMART®SIMPLEX PANELS

Oil Smart® Simplex panel with 20 Amp Motor start relay, and mounting hardware. High Liquid red light and audible alarm 83 decibels buzzer, auxiliary dry contacts. Yellow light to indicate the presence of oil with auxiliary dry contacts, white light to indicate the presence of water with auxiliary dry contact. Alarm test and silence switch automatic reset. Hand-Off Auto (HOA) switch for manual pump control. Green light indicates motor run. Complete with, Oil Smart® Controller with 6" sensor and 20' cord, and Liquid Smart® sensor with 20' cord. NEMA 4X Enclosures. Optional Total Pump Protection Feature (TP): Circuit Breaker, no-load or overload lockout, pump fault red light (water seals, overheat, etc.), and pump reset.

Model# Single Phase	Suggested Retail
#OSSIM-30 0-3 HP 120/208/240	\$1,221.00
#OSSIM-30-CB 0-3 HP 120/208/240 Includes Circuit Breaker	\$1,296.00

TOTAL PUMP PROTECTION SIMPLEX PANELS (Include circuit breaker, no load and overload lockout, pump fault features including pump fault dry contacts, and pump fault red light)

Model# Single Phase	Suggested Retail
#OSSIM-TP-1 0-3 HP 120/208/240	\$1,545.00

Model# Three Phase	Suggested Retail
#OSSIM-TP-3 0-3 HP 120/208/240VAC	\$1,680.00
#OSSIM-TP-3-B 0-7 HP 480VAC	\$1,905.00

OIL SMART®DUPLEX PANELS

Oil Smart® Duplex panel SEEwater's all in one circuit board with solid state motor rotating relay, high demand two pump operation, motor seal sensors, and the Oil Smart® alarm circuit complete with two (2) 20 Amp Motor start relays, and mounting hardware. Oil Smart® Pump Controller, and Liquid Smart® Alarm Sensor. High Liquid red light and audible alarm (83 decibels buzzer), auxiliary dry contacts. Yellow light to indicate presence of oil, with auxiliary dry contacts, white light to indicate the presence of water, with auxiliary dry contact. Alarm test and silence switch automatic reset. Two (2) Hand-Off Auto (HOA) switches for manual pump control. Two Green lights indicates motor #1 and motor#2 run. Complete with, Oil Smart® Controller with 6" sensor and 20' cord, Liquid Smart® sensor with 20' cord, and High Water 2 Pump Demand Switch with 20' cord. NEMA 4X Enclosures.

2007-2008 Price Sheet Detailed

Model#	Single Phase	Suggested retail
---------------	---------------------	-------------------------

OSSDIP-3	0-3 HP 110/208/240 VAC	\$1,725.00
----------	------------------------	------------

Model # Three Phase

OSSD3P-5	0-5 HP 208/240VAC	\$2,085.00
----------	-------------------	------------

OSSD3P-10	0-10 HP 480VAC	\$2,310.00
-----------	----------------	------------

NOTE: All Simplex and Duplex Panels (except for Model # OSSM-30) have an optional Dial-An-Amp Feature: One or Two-Pump motor lockout protection, select the lockout amps suitable for your specific pump needs. Please consult the factory for proper amp selection. **Add a -D** to model # when ordering Dial-An-Amp

Custom Simplex and Duplex Panels are also available in plastic, steel, and stainless steel. Please consult the factory for custom panel options.

Oil Smart Travel Float Assembly

The Oil Smart® Travel Float is an oil prevention pump control system that provides an automatic water pump control in dewatering applications with the capability of a large pumping range between on and off. The Oil Smart® Travel Float System is effective in any size small or large sump, tank, or containment structure adjustable by inserting high and low stop pins as the square PVC system floats up and down a stationary stainless steel post. Standard models available include an assembly of 48" or 72" of pumping range, with adjustable holes for the start and stop pins. The pumping range can be extended beyond 72" upon request. Use in conjunction with any Oil Smart products and SEewater will pre-assemble the travel float system.

Model#	Suggested Retail
---------------	-------------------------

TFA-48 48" Pumping Range	\$1035.00
--------------------------	-----------

TFA-72 72" Pumping Range	\$1087.00
--------------------------	-----------

2007-2008 Price Sheet Detailed

Wastewater/Sewage Control Panels

WASTEWATER/SEWAGE SIMPLEX PANELS

Wastewater Simplex Panels come with a 20 Amp motor start relay in single or three-phase configuration. Includes one normally open pump duty dual float switch with 30' cord (pump on "start", pump off "stop") and one narrow-angle float switch with 20' cord (high liquid alarm). Includes Hands-Off-Auto (H.O.A.) Switch, green motor run light, red beacon alarm light with high 84 decibel external alarm and dry contact, alarm test and silence buttons with automatic rest, and complete mounting hardware. NEMA 4X Enclosures. Optional Total Pump Protection Feature (TP): Circuit Breaker, no-load or overload lockout, pump fault red light (water seals, overheat, etc.), and pump reset.

Model# Single Phase	Suggested Retail
----------------------------	-------------------------

#WS1P 0-3 HP 110/208/240 VAC	\$697.50
------------------------------	----------

#WS1P-TP 0-3 HP 110/208/240 VAC	\$840.00
---------------------------------	----------

Model# Three Phase	Suggested Retail
---------------------------	-------------------------

#WS3P-TP 0-7 HP 480VAC	\$1125.00
------------------------	-----------

WASTEWATER/SEWAGE DUPLEX PANELS

Wastewater Simplex Panels come with a 20 Amp motor start relay in single or three-phase configuration. Includes three or four floats (pump on "start", pump off "stop", high liquid alarm/two-pump operation or pump on "start", pump off "stop", high liquid alarm, and two-pump operation). Includes Hands-Off-Auto (H.O.A.) Switch, green motor run light, red beacon alarm light with high 84 decibel external alarm and dry contact, alarm test and silence buttons with automatic rest, and complete mounting hardware. Also includes circuit breakers, no-load or overload lockout, pump fault red lights (water seals, overheat, etc.), and pump reset. NEMA 4X Enclosures.

Model# Single Phase	Suggested Retail
----------------------------	-------------------------

#WS1P-3 0-3 HP 110/208/240VAC	\$867.00
-------------------------------	----------

#WD1P-4 0-3 HP 110/208/240VAC	\$1092.00
-------------------------------	-----------

Model# Three Phase	Suggested Retail
---------------------------	-------------------------

#WS3P-5-3 0-5 HP 208/240VAC	\$1305.00
-----------------------------	-----------

#WD3P-5-4 0-5 HP 208/240VAC	\$1372.50
-----------------------------	-----------

#WD3P-10-3 0-10HP 480VAC	\$1408.50
--------------------------	-----------

#WD3P-10-4 0-10HP 480VAC	\$1476.00
--------------------------	-----------

NOTE: All Simplex and Duplex Panels (except for Model # WS1P) have an optional Dial-An-Amp Feature: One or Two-Pump motor lockout protection, select the lockout amps suitable for your specific pump needs. Please consult the factory for proper amp selection. **Add a -D** to model # when ordering Dial-An-Amp

Custom Simplex and Duplex Panels are also available in plastic, steel, and stainless steel. Please consult the factory for custom panel options.
